

OPPOSED FREELY CUTTABLE (PLASTIC FIBER) CONSTRUCTIONS

Here we offer geometries for the 0.5 mm and 1 mm jacketed plastic fibers. They are freely cuttable by razor or hot knife. All of the 0.5 mm fibers are furnished with ferrules for adapting to the 2.2 mm photoelectric apertures. Geometries with extended stainless steel probes can be lengthened or shortened to suite your needs.

Order codes SP05-T4, SP1-T4, SP05-LT4, SP1-LT4 include the M2.6X.45 threaded tip so that the available small Japanese lens can be attached.

OPPOSED FREELY CUTTABLE CONSTRUCTIONS

STANDARD CABLE LENGTH (L) 2 m, CUSTOM LENGTHS AVAILABLE
 UNLESS OTHERWISE NOTED, ILLUSTRATIONS ARE FULL SCALE, DIMENSIONS ARE IN INCHES

<p>ORDER CODE / SP05 T3</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M3P0.5</p>	<p>ORDER CODE / SP05 T4</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M4P0.7 M2.6P0.45</p>	<p>ORDER CODE / SP1 T4</p> <p>SINGLE 1 mm JACKETED FIBER</p> <p>M4P0.7 M2.6P0.45</p>
<p>ORDER CODE / SP05 LT3</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>0.059" O.D. 3/16" RADIUS M3P0.5</p>	<p>ORDER CODE / SP05 LT4</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>0.059" O.D. 3/16" RADIUS M4P0.7 M2.6P0.45</p>	<p>ORDER CODE / SP1 LT4</p> <p>SINGLE 1 mm JACKETED FIBER</p> <p>0.109" O.D. 3/16" RADIUS M4P0.7 M2.6P0.45</p>
<p>ORDER CODE / SP05 TL3</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M3P0.5 0.036" O.D. 3/16" RADIUS</p>	<p>ORDER CODE / SP05 TB3</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M3P0.5 0.036" O.D. BENDABLE TUBING</p>	
<p>ORDER CODE / SP05 TL4</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M4P0.7 0.059" O.D. 3/16" RADIUS</p>	<p>ORDER CODE / SP05 TB4</p> <p>SINGLE 0.5 mm JACKETED FIBER</p> <p>M4P0.7 0.059" O.D. BENDABLE TUBING</p>	
<p>ORDER CODE / SP1 TL4</p> <p>SINGLE 1 mm JACKETED FIBER</p> <p>M4P0.7 0.059" O.D. 3/16" RADIUS</p>	<p>ORDER CODE / SP1 TB4</p> <p>SINGLE 1 mm JACKETED FIBER</p> <p>M4P0.7 0.059" O.D. BENDABLE TUBING</p>	